

AR34

Loosening, Separating, Transporting



**WACKER
NEUSON**
all it takes!



First class performance

The AR34 ensures sustained performance such that e.g. the materials are sifted continuously and thoroughly. Slow running external vibrators (like the AR34 with 3,000 rpm) are ideally suited for such operations.

- Excellent power-to-weight ratio.
- High operating reliability and long service life due to its extremely robust design
- Finely adjustable centrifugal forces via adjustable eccentric weight discs.
- Vibration resistant design
- Well-protected and centered cable feed.

AR34 Technical specifications

AR34/3/400*

| | |
|------------------------|--------------------|
| Vibrations | 3,000 rpm |
| Frequency | 50 Hz |
| Centrifugal force max. | 3.47 kN |
| Rated voltage 3~ | 400 V |
| Rated current | 0.75 A |
| Engine performance | 0.4 kW |
| L x W x H | 295 x 151 x 134 mm |
| Weight | 7 kg |
| Fastening | 120 x 120 mm |

* No power cable included in this product.

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2021 Wacker Neuson SE.