

AR63 series

Concrete Compaction in prefabricated concrete factories



**WACKER
NEUSON**
all it takes!



Made for sustained use: AR63

Above all the AR63 offers this: Long service life and minimum maintenance. This is due to the vibration and heat resistant windings of the electric motor (plastic sealing, Class H up to 180 °C) as well as the extremely robust special bearings. For that reason, the AR63 is perfectly designed for use in precast factories.

- Powerful and reliable performance
- High operating reliability and long service life due to its extremely robust design
- Finely adjustable centrifugal forces via adjustable eccentric weight discs
- Vibration resistant design
- Fastened with a flange

AR63 series Technical specifications

AR63/6/250*

Vibrations	6,000 rpm
Frequency	200 Hz
Standard centrifugal force	10.36 kN
Centrifugal force max.	19.03 kN
Rated voltage 3~	250 V
Rated current	3.3 A
Engine performance	1.25 kW
L x W x H	231 x 188 x 188 mm
Weight	13.9 kg
Fastening	90 x 154 mm

* No power cable included in this product.

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.
Copyright © 2021 Wacker Neuson SE.