

BH55

Gasoline Breakers



**WACKER
NEUSON**
all it takes!



The entry-level model for demolition

The BH55 gasoline demolition breaker is the entry-level model among demolition breakers. Lighter and smaller than the other demolition breakers in the Wacker Neuson series, it is designed for professional use and impresses with its compact size and ease of use.

- 55 joules of single stroke impact energy
- 1,300 blows per minute
- Economical and low-emission Wacker Neuson motor of in-house design
- Simple percussion system maintenance on site with a small grease gun over the central zerk fitting
- Shanks for all common tools

BH55 Technical specifications

| | ∅ 27 x 80 | hex 25 x 108 | hex 28 x 160 |
|------------------------------|-----------------|-----------------|-----------------|
| Single stroke energy J (mkp) | 55 | 55 | 55 |
| Percussion rate 1/min | 1300 | 1300 | 1300 |
| Weight kg | 22.8 | 22.7 | 23.8 |
| L x W x H mm | 777 x 492 x 346 | 791 x 492 x 346 | 833 x 492 x 346 |
| Engine / Motor manufacturer | Wacker Neuson | Wacker Neuson | Wacker Neuson |
| Engine / Motor type * | WM80c | WM80c | WM80c |
| Displacement cm ³ | 80 | 80 | 80 |
| Engine performance kW | 1.6 | 1.6 | 1.6 |
| RPM / speed rpm | 4,250 | 4,250 | 4,250 |
| Gasoline / oil mixture | 50:1 | 50:1 | 50:1 |
| Tank capacity l | 1.8 | 1.8 | 1.8 |
| Fuel consumption l/h | 0.9 | 0.9 | 0.9 |
| CO2 (NRSC) ** g/kWh | 1,113 | 1,113 | 1,194 |

* Air-cooled, single cylinder, two-cycle gasoline engine **Determined value of the CO2 emission during engine certification without consideration of the application on the machine.

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.
Copyright © 2021 Wacker Neuson SE.