

GS12AI

Portable Generators



**WACKER
NEUSON**
all it takes!



All-rounder with added safety features

When it comes to supplying electricity, the portable generators of the G-range are the all-rounders. They provide reliable power for construction, industrial, commercial, agricultural and D-I-Y applications. They are equipped with added safety features for the protection of the user.

- Both models are equipped with an isolation monitor, which provides added security for the operator.
- The GS 12AI has an extremely high reserve capacity: It can handle equipment with a starting current of up to 4 times the nominal current value.
- The Honda 4-cycle engine impresses with its easy start, reliable strong performance, and a long service life.
- The large capacity tank ensures long run times between fills.

GS12AI Technical specifications

Dimensions

L x W x H	960 x 640 x 667 mm
Net weight	165 kg

Operating data

Output performance (max.)	13.4 kW
Continuous output at 1~	6 kW
Continuous output at 3~	12 kW
Rated current at 1~	27.1 A
Rated current at 3~	17.1 A
Rated voltage at 1~	230 V
Rated voltage at 3~	400 V
Circuit breaker 3~	16 A
Receptacles	2 x Schuko 230 V, 16 A - 1 x CEE 230 V, 16 A - 1 x CEE 400 V, 16 A

Electrical system

Frequency	50 Hz
Power factor	1 cos Φ 1~
Power factor	0.8 cos Φ 3~

Engine / Motor

Engine / Motor	GX630
Engine / Motor manufacturer	Honda
Displacement	688 cm ³
Tank capacity (fuel)	24 l
Fuel consumption	5.9 l/h
Runtime (at continuous output)	4.8 h

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2021 Wacker Neuson SE.