

IRSE-FU

Premium Line Internal Vibrator



**WACKER
NEUSON**
all it takes!



Comfortable and flexible: the IRSE-FU series

Intelligent technology developed by Wacker Neuson: The integrated frequency converter of the high-frequency internal vibrator series IRSE-FU is simply convincing. It provides a much more independent operation without the necessity of an external converter. In addition the very practical guide handle of the IRSE-FU series also provides great user comfort.

- Integrated frequency converter
- Comfortable Low Vib guide handle
- Sealed electronics
- Reliable operation, even if the input voltages fluctuate and when used with generators
- All components 'Made in Germany'

IRSE-FU Technical specifications

	IRSE-FU45	IRSE-FU58
Diameter of the vibrator head mm	45	58
Length of the vibrator head mm	382	400
Weight of the vibrator head kg	3.5	5.8
Operating weight kg	15	17
Effective diameter * cm	60	85
Vibrations rpm	12,000	12,000
Engine / Motor	High-frequency squirrel-cage induction motor with integrated electronic frequency converter in the switch box	High-frequency squirrel-cage induction motor with integrated electronic frequency converter in the switch box
Voltage 1~ V	220 - 240	220 - 240
Current A	4.8	6
Frequency Hz	50 - 60	50 - 60
Hose (Protective hose) m	0.3 / 0.8	0.3 / 0.8
Power cable m	15	15
Feed cable m	0.5	0.5

* This is a non binding indication, based on practical experience of our customers under certain operating conditions. For special conditions this value may vary. We recommend that you first perform a test under operating conditions.

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2021 Wacker Neuson SE.