



## PG3A

### Dewatering Pumps of the PG series

Clear water from your job site or swimming pool quickly with Wacker Neuson dewatering pump.

With its self-priming centrifugal pumping action and overall compact size, the pump is ideal for the contractor with the need for temporary water removal.

## Highlights

- Pump out vanes on back of impeller.
- Cast iron impeller and volute for long life and minimal service
- Carbon ceramic mechanical seal.

## Technical Data

### ■ Mechanical - Output Details

Flow rate max.	1,000.0 l/min
Solid diameter max.	6.5 mm
Suction head max.	7.5 m
Delivery height max.	27.0 m

### ■ Mechanical Details

Length	515.0 mm
Width	405.0 mm
Height	460.0 mm
Operating weight	29.0 kg
Intake-/Pressure socket-dia.	75.0 mm

### ■ Engine

Cooling	air cooling
---------	-------------

Motor type	Gasoline engine
Cylinder	1.0
Cylinder capacity	163.0 cm <sup>3</sup>
Fuel type	Gasoline
Fuel consumption	1.8 L/hr
Tank capacity	3.6 l
Oil filling max.	0.6 l
Power rating max.	3.6 KW
Engine speed (Power max.)	3,600.0 1/min
Operating Engine speed	3,600.0 1/min
Manufacturer	Honda
Fuel consumption at full power	1.8 L/hr
Running time at 100%	2.1 hrs