# PS4-11003HH

## Submersible Pump

powerful and reliable for construction site dewatering

The robust PS series three-phase submersible pumps can handle wastewater containing solids up to a diameter of 20 mm. They feature a high flow rates and high heads, making them ideal for applications where it is important to dry out construction sites quickly and reliably. These high-quality pumps are extremely durable and easy to use. The PS series are also offered in lightweight aluminum models and automatic versions.

## Highlights

- Model variations
- Optional motor protection plug for three-phase pumps
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Oil lifter for reliable lubrication in any situation
- Safe to run dry
- Steel sleeve reduces wear of the shaft

## Technical Data

### Electrical - Output Details

| | |
|---|---|
| Nominal current | 22.00 A |
| Nominal voltage | 400.0 V |
| Nominal frequency | 50.0 Hz |
| Phase | 3.0 ~ |

### Mechanical - Output Details

| | |
|---|---|
| Flow rate max. | 1,440.0 l/min |
| Solid diameter max. | 12.0 mm |
| Delivery height max. | 48.5 m |

### Mechanical Details

| | |
|---|---|
| Length | 375.0 mm |
| Width | 350.0 mm |
| Height | 805.0 mm |
| Operating weight | 130.0 kg |
| Intake-/Pressure socket-dia. | 100.0 mm |

### Motor

| | |
|---|---|
| Nominal speed | 2,910.0 1/min |

### Electrical System

| | |
|---|---|
| Length Cable | 20.0 m |
| Cable cross-section | 4.0 mm² |

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.


Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com